

DRYDENE TRANSALL HD TRANSMISSION FLUID

TRANSMISSION/AUTOMATIC TRANSMISSION FLUID



PRODUCT DESCRIPTION

DRYDENE TRANSALL HD TRANSMISSION FLUID is premium fluid for use in passenger car and light truck automatic transmissions. It is specially formulated with advanced friction modifiers to provide smooth operation and long service life in both automotive and other applications requiring a multi-purpose transmission fluid.

PRODUCT APPLICATION

DRYDENE TRANSALL HD TRANSMISSION FLUID is recommended for use in a wide range of transmission and power transfer applications:

- Suitable for use in passenger cars and light-duty trucks where the GM DEXRON III® or Ford Mercon® fluids are specified
- Power steering units specifying automatic transmission fluid.
- Heavy-duty trucks, buses, coaches and off-highway vehicles.
- Hydrostatic transmissions and hydraulic systems specifying automatic transmission fluid.

FEATURES AND BENEFITS

DRYDENE TRANSALL HD TRANSMISSION FLUID is a blend of premium base oils and specially selected additives and friction modifiers to provide smooth performance, thermal stability and wear protection.

- Protects vital transmission components against sludge, varnish and harmful deposit formations that can reduce useful life and performance.
- Heavy-duty antioxidant, anti-wear and viscosity improver additive package ensures smooth, consistent shifting in both low and high temperature settings.
- Shear stable chemistry helps to extend service life and maintenance intervals in both light duty and heavy-duty/heavily loaded transmissions.



SPECIFICATIONS

- **Allison** C-4, meets TES-389
- **DEXRON III G/H, DEXRON II, DEXRON, AW 1**
- **MERCON** Ford ESP-M2C166-H

Other applicable uses may exist. Please contact DRYDENE Performance Products for more information.

rev Aug 2017



DRYDENE TRANSALL HD TRANSMISSION FLUID

TRANSMISSION/AUTOMATIC TRANSMISSION



TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	TRANSALL HD ATF
Viscosity @ 100°C cSt	ASTM D445	7.39
Viscosity @ 40°C cSt	ASTM D445	35.70
Viscosity Index	ASTM D2270	180
Brookfield Viscosity @ -40°C, cP	ASTM D2983	18,500
Color	ASTM D1500	Red
Copper Strip Corrosion (3 hrs @ 100°C)	ASTM D130	1B
Foam Test	ASTM D892	<100/0 ml
Gravity, °API	ASTM D287	32.97
Hydrolytic Stability Test	ASTM D2619	Pass
Pour Point °C	ASTM D5950	-50
Rust Protection	ASTM D665A	Pass
Specific Gravity @ 60°F (15.6 °C)	ASTM D4052	0.8604
Sunstrand Axial Piston Pump		Pass

All stated physical properties are typical of standard production and may vary.

DON'T GO THE EXTRA MILE, GO THE EXTRA THOUSAND

Over the past 100 years, we've crushed rocks, built highways, toiled in fields and hauled more cargo than you can imagine. We have no plans of stopping anytime soon, and neither do you.

DRYDENE stands for integrity, quality and loyalty. Our company has over a century of heritage to back it up. We deliver high-quality lubricants that exceed expectations and set higher industry standards overall, because your lubricants should stand the test of time.

All DRYDENE heavy-duty and passenger car engine oils, hydraulic fluids, transmission and gear oils, greases as well as our extensive lineup of industrial and specialty fluids are formulated to be as rigorous as the work that needs to be done.

DRYDENE Performance Products
Toll-free: 1-877-DRYDENE
info@drydenelubricants.com
www.drydenelubricants.com

HEALTH AND SAFETY

This product is not expected to have any adverse health implications when used for its intended purposes. Always wear protective gloves when handling used oil and dispose of properly. Avoid contact with skin and wash immediately with soap and water should any contact occur.

For a copy of this product's Safety Data Sheet (SDS), contact DRYDENE Performance Products at 1-877-DRYDENE.

DISCLAIMER

Always follow OEM recommendations for fluid viscosity and API service category. DRYDENE Performance Products assumes no responsibility for product misuse or improper application.

rev Aug 2017

