

Product identifier used on the label: DRYDENE MULTI-VISCOSITY HYDRAULIC 46

Stock Number: D31246 Revision Date: 08-29-2017

Replaces:

1. Identification

Product identifier used on the label: DRYDENE MULTI-VISCOSITY HYDRAULIC 46

Stock Number: D31246

Other means of identification:

Synonyms: No data available

Recommended use of the chemical and restrictions on use:

Recommended use: Hydraulic Oil

Restrictions on use: Uses other than those described above

Name, address, and telephone number

of the chemical manufacturer,

importer, or other responsible party:

Drydene Performance Products

305 Micro Drive

Jonestown, PA 17038

Phone number: 1-877-DRYDENE

E-mail address: sds@drydenelubricants.com

Emergency phone number: CHEMTREC: +1 (800) 424-9300 International: +01 (703) 527-3887

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

GHS Classification: Not classified as hazardous under OSHA

Hazards not otherwise classified: No data available

% unknown toxicity (Inhalation Gas):
% unknown toxicity (Inhalation Vapor):
% unknown toxicity (Inhalation Dust):
70.639963 % of the mixture consists of ingredient(s) of unknown toxicity.
70.639963 % of the mixture consists of ingredient(s) of unknown toxicity.
70.639963 % of the mixture consists of ingredient(s) of unknown toxicity.

3. Composition/information on ingredients

| Chemical Name | Common name and synonyms | CAS# | % |
|--------------------------|--------------------------|------|---|
| Not classified under GHS | | | |

One or more hazardous ingredient(s) is claimed as a trade secret under the OSHA Hazard Communication Standard. The hazards of this (these) ingredient(s) are given on this SDS.

4. First-aid measures

Product identifier used on the label: DRYDENE MULTI-VISCOSITY HYDRAULIC 46

Stock Number: D31246 Revision Date: 08-29-2017

Replaces:

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual

administer oxygen.

Eye Contact: Use eye wash to remove a chemical from the eye. Flush the affected eye

for at least fifteen minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical attention if

irritation persists.

Skin Contact: Wash with soap and water. Get medical attention if irritation develops or

persists. Seek medical advice if symptoms persist.

Ingestion: Minimal risk of harm if swallowed. Do not induce vomiting. Seek medical

attention immediately. Provide medical care provider with this SDS.

Most important symptoms/effects,

acute and delayed:

None Known

Indication of immediate medical attention and special treatment

needed, if necessary:

Aspiration during swallowing or vomiting may severely damage the lungs. If evacuation of stomach contents is necessary, use method least likely to

cause aspiration.

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting

fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the

fire. Do not direct a stream of water into the hot burning liquid.

Unsuitable extinguishing media: No data available

Specific hazards arising from the

chemical:

No data available

Hazardous combustion products: Carbon monoxide, Smoke

Special protective equipment and

precautions for fire-fighters:

No data available

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

No health affects expected from the clean up of this material if contact can be avoided. Follow personal protective equipment recommendations

Product identifier used on the label: DRYDENE MULTI-VISCOSITY HYDRAULIC 46

Stock Number: D31246 Revision Date: 08-29-2017

Replaces:

found in Section 8 of this SDS.

Methods and materials for containment and cleaning up:

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations.

Used fluid should be disposed of at a recycling center.

7. Handling and storage

Precautions for safe handling:

Safe storage conditions:

Mildly irritating material. Avoid unnecessary exposure. No data available

Conditions for safe storage, including

any incompatibilities:

Store in a cool dry place. Isolate from incompatible materials.

Materials to Avoid/Chemical

Incompatibility:

Strong oxidizing agents

8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

| Chemical component | OSHA PEL | ACGIH TLV | ACGIH STEL | IDLH |
|--------------------|----------|-----------|------------|------|
| No data available | | | | |
| | | | | |

Appropriate engineering controls:

Use local exhaust ventilation or other engineering controls to minimize

exposures and maintain operator comfort.

Individual protection measures, such as personal protective equipment:

Respiratory Protection: Respiratory protection may be required to avoid overexposure when

handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. None

required where adequate ventilation is provided. If airborne concentrations are above the applicable exposure limits, use

NIOSH/MSHA approved respiratory protection.

Respirator Type(s): None required where adequate ventilation is provided. If airborne

concentrations are above the applicable exposure limits, use

Safety Data Sheet Product identifier used on the label: DRYDENE MULTI-VISCOSITY HYDRAULIC 46

Stock Number: D31246 **Revision Date: 08-29-2017**

Replaces:

NIOSH/MSHA approved respiratory protection.

Eye protection: No special requirements under normal industrial use.

Skin protection: Where use can result in skin contact, practice good personal hygiene and

wear impervious gloves. Wash hands and other exposed areas with mild

soap and water before eating, drinking, and when leaving work.

Gloves: Neoprene, Nitrile

General hygiene conditions: No data available

9. Physical and chemical properties

Appearance (physical state, color etc.):

Physical state: Liquid Color: Beige Odor: Mild

Odor Threshold: Not determined pH: No data available

Melting point/freezing point:

No data available **Melting Point:** Freezing point: No data available

Initial boiling point and boiling range

(°C):

226

150

No data available **Evaporation Rate:** Flammability (solid, gas): No data available

Upper/lower flammability or explosive

limits:

Upper flammability or explosive

limits:

Flash Point (°C):

Not established

Lower flammability or explosive

limits:

Not established

Vapor pressure: No data available Vapor density: No data available

Relative density: 0.86

Solubility(ies): Negligible; 0-1%

Safety Data Sheet Product identifier used on the label: DRYDENE MULTI-VISCOSITY HYDRAULIC

Stock Number: D31246 **Revision Date: 08-29-2017**

Replaces:

Partition coefficient: n-octanol/water: No data available **Auto-ignition temperature:** No data available **Decomposition Temperature:** Not determined

Viscosity: 44.86 cSt @ 40°C

Volatile organic compound (VOC)

content and percentage of volatiles:

10. Stability and reactivity

Reactivity:

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: None expected under standard conditions of storage.

0.000000

Conditions to avoid (e.g., static discharge, shock, or vibration):

Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition.

Moisture (will lead to product performance degradation).

Incompatible materials: Strong oxidizing agents

Hazardous decomposition products: Carbon monoxide, Smoke, Carbon monoxide, sulfur oxides, aldehydes,

and other petroleum decomposition products in the case of incomplete

combustion. Oxides of nitrogen, phosphorus, calcium, copper, magnesium, sodium, and hydrogen sulfide may also be present.

11. Toxicological information

Description of the various toxicological (health) effects and the available data used to identify those effects:

Information on the likely routes of exposure (inhalation, ingestion, skin

and eye contact):

No data available

Symptoms related to the physical,

chemical and toxicological

characteristics:

None Known

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Ingestion Toxicity: Although this product has a low order of acute oral toxicity, aspiration of

minute amounts into the lungs during ingestion or vomiting may cause

mild to severe pulmonary injury and possibly death.

Skin Contact: This material is likely to be slightly irritating to skin based on animal

data. Can cause minor skin irritation, defatting, and dermatitis.

Safety Data Sheet Product identifier used on the label: DRYDENE MULTI-VISCOSITY HYDRAULIC

Stock Number: D31246 **Revision Date:** 08-29-2017

Replaces:

Absorption: Likely to be practically non-toxic based on animal data.

Inhalation Toxicity: No hazard in normal industrial use. Likely to be practically non-toxic

based on animal data.

Eye Contact: This material is likely to be non-irritating to eyes based on animal data.

Sensitization: No data available

No data available to indicate product or any components present at Mutagenicity:

greater than 0.1% is mutagenic or genotoxic.

Carcinogenicity: Not expected to cause cancer. This product meets the IP-346 criteria of

<3% PAH's and is not considered a carcinogen by the International

Agency for Research on Cancer.

STOT-single exposure: Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met. STOT-repeated exposure:

Based on available data, the classification criteria are not met. **Aspiration hazard:**

Other information: No data available

Numerical measures of toxicity (such as acute toxicity estimates):

| Chemical Nam | ne LD50 Oral | LD50 Dermal | LC50 Inhalation |
|-----------------|--------------|-------------|-----------------|
| No data availab | ole | | |

Is the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA:

| Chemical Name | OSHA Carcinogen | IARC Carcinogen | NTP Carcinogen |
|----------------------------|-----------------|-----------------|----------------|
| There are no components | | | |
| that are known or reported | | | |
| to cause cancer. | | | |

12. Ecological information

Ecotoxicity (aquatic and terrestrial,

No data available

where available):

Ecological Toxicity Data:

| Chemical Name | CAS# | Aquatic EC50 Crustacea | Aquatic ERC50 Algae | Aquatic LC50 Fish |
|-------------------|------|---------------------------|------------------------|-------------------|
| No data available | | | | |

Product identifier used on the label: DRYDENE MULTI-VISCOSITY HYDRAULIC 46

Stock Number: D31246 Revision Date: 08-29-2017

Replaces:

Persistence and degradability:Biodegrades slowly.

Bioaccumulative potential: Bioconcentration may occur.

Mobility in soil: This material is expected to have essentially no mobility in soil. It absorbs

strongly to most soil types.

Other adverse effects (such as

hazardous to the ozone layer):

No data available

13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated

packaging:

Spent or discarded material is non-hazardous according to environmental

regulations.

Contaminated packaging: Recycle containers whenever possible.

14. Transport information

Carriage of dangerous goods by road (DOT), rail or inland waterways:

DOT Basic Description: Not classified as hazardous for transport (DOT, TDG, IMO/IMDG,

IATA/ICAO).

International carriage of dangerous goods by sea (IMDG/IMO):

UN number: Not regulated by IMDG

UN Proper shipping name:

Transport hazard class(es):

Packing group, if applicable:

Not applicable

Not applicable

International carriage of dangerous goods by air (IATA):

UN number: Not regulated by IATA

UN Proper shipping name:

Transport hazard class(es):

Packing group, if applicable:

Not applicable

Not applicable

Environmental hazards (e.g., Marine None.

Product identifier used on the label: DRYDENE MULTI-VISCOSITY HYDRAULIC 46

Stock Number: D31246 Revision Date: 08-29-2017

Replaces:

pollutant (Yes/No)):

Transport in bulk (according to Annex II

No data available

of MARPOL 73/78 and the IBC Code):

Special precautions which a user needs to be aware of or needs to comply with in connection with transport or

in connection with transport or conveyance either within or outside

their premises:

No data available

15. Regulatory information

Safety, health and environmental regulations specific for the product in question:

TSCA Status: All components of this material are on the US TSCA Inventory or are

exempt.

Regulated Components:

| Chemical Name | CAS# | CERCLA | Sara EHS | Sara 313 | U.S. HAP |
|------------------------|------------|--------|----------|----------|----------|
| Petroleum distillates, | | | | | |
| solvent dewaxed | 64742-65-0 | N | N | N | N |
| heavy paraffinic | | | | | |
| Petroleum distillates, | | | | | |
| hydrotreated heavy | 64742-54-7 | N | N | N | N |
| paraffinic | | | | | |

| Chemical Name | CAS# | California Prop 65 - Cancer | California Prop 65 - Dev. Toxicity | California Prop 65 - Reprod fem | California Prop 65 - Reprod male |
|---|------------|--------------------------------|---------------------------------------|------------------------------------|-------------------------------------|
| Petroleum distillates, solvent dewaxed heavy paraffinic | 64742-65-0 | N | N | N | N |
| Petroleum distillates, hydrotreated heavy paraffinic | 64742-54-7 | N | N | N | N |

| Chemical Name | CAS# | Massachusetts RTK List | New Jersey RTK List | Pennsylvania RTK List | Rhode Island RTK List | Minnesota Hazardous Substance List |
|------------------------|------------|---------------------------|------------------------|--------------------------|-----------------------------|---|
| Petroleum distillates, | 64742-65-0 | N | N | N | N | N |

Product identifier used on the label: DRYDENE MULTI-VISCOSITY HYDRAULIC 46

Stock Number: D31246 Revision Date: 08-29-2017

Replaces:

| solvent dewaxed heavy paraffinic | | | | | | |
|----------------------------------|------------|---|---|---|---|---|
| Petroleum distillates, | | | | | | |
| hydrotreated heavy paraffinic | 64742-54-7 | N | N | N | N | N |

16. Other information, including date of preparation or last revision.

SDS Prepared by: DSTOVER

Revision Date: 08-29-2017

Revision Number: 1.0

Reason for revision:NEW VERSIONReferences:No data availableOther Info:No data available

Disclaimer: This safety data sheet and the information it contains is offered to you in

good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct, but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents.

No warranty is made, either expressed or implied.